

STEEL ROLLING WAREHOUSE LADDERS

GSW SERIES




Trusted by the Pros for Over 60 Years


Louisville Ladder steel rolling warehouse ladders are considered one of the best on the market. Ladder equipped with ball bearing casters allowing easy movement to any area. Rugged all steel construction. Sturdy handrails, easy 56 degree climbing angle, "Sure Grip" tread, 7" deep steps and 10" deep top platform provide quality features for the everyday user.

ALL SIZES MEET OR EXCEED THE REQUIREMENTS OF ANSI A14.7 AND OSHA 1910.29 STANDARDS WITH A

350 lbs. load capacity*
*Maximum Load Capacity



Spring Loaded Casters
(standard on 2-step to 5-step models) Four spring loaded casters on 2-5 step models. Casters retract when load is placed on the ladder, setting the ladder firmly in place on rubber tips. When the load is removed, springs push down the casters enabling the ladder to move about freely.



Locking Device
(standard on 6-step to 15-step models) Models 6-step and taller come equipped with a large 4" swivel caster in front and rigid casters in the rear. Stepping on bottom step activates the locking mechanism, locking rubber tipped feet in down position. To move the ladder, just step on the unlocking pedal.



No Forward Descent
56 degree climbing angle does not meet ANSI requirements for forward descent.



Toeboard
(standard on 12-step to 15-step models) The top platform on models 12-step and taller is surrounded on three sides by a 4" high toeboard. Can be added as an option to smaller size models. (W05)




Premium Powder Paint
Baked-on finish is durable and provides superior scratch and scuff resistance. Attractive, even coverage with no drips or runs.


OPTIONS & ACCESSORIES




Extra Deep Top
Standard top platform is 10" deep. 16" and 24" wide models can also be manufactured with an extra deep top platform measuring 20" or 30".
Accessory # W01 (20")
Accessory # W02 (30")



Handrail & Guardrail
Models 5-step and taller come standard with 30" handrails and 36" guard-rails on back. Also available on 3-4 step models.
Accessory #W03



Spring Loaded Casters
(option for 1-step model only) 1-step model comes standard with four rubber tipped legs for stability. Also available with spring loaded casters like those used on 2-5 step models.
Accessory # W04



Handrail & Outrigger (accessory)
Required when local codes require 3:1 height to base ratio.

GSW SERIES
5 Step (16" Wide Only) GRCAL05EC-B
5-9 Step GRCAL0509-B
10-12 Step GRCAL1012-B
13-15 Step GRCAL1315-B

GSW REPLACEMENT PARTS

MODEL	DESCRIPTION	SIZE
999844A	Step Lock Spring	6'-15'
601054A	2" Rubber Pad	6'-15'
921016	Caster	1'-5'
999928A	Front Crutch Tip	1'-5'
999928B	Back Crutch Tip	1'-5'
921004A	4" Swivel Caster	6'-15'
921007A	4" Rigid Caster w/Stud	6'-15'

*GSW parts are not interchangeable with SW parts



GSW2410



GSW2405



GSW1601A



GSW1603A

